

Tel: 01283 551050 Email: Sales@PHFlexible.com Web: www.PackagingGB.co.uk

Saving MPSSemi-Auto Stretch Wrapper Power Stretch Film Carriage



- Table Ø 1650mm, 6mm plate, for pallets up to 1200x1000mm
- Capacity: up to 20 pallets/hour depending on load size
- Wrapping height: up to 2200mm (incl. pallet)
- Max. weight: 2000kg

FEATURES

Powered Film Carriage for pre-stretch system (up to 250%)

Suitable for power-stretch film

Photocell for automatic height detection

Soft start and stop by frequency inverter, with return to start position

4 wrapping programs: single, crosswrap, cross-plus, full independently adjustable top & bottom reinforcement wraps

Reinforcement wraps at any point in the cycle

Wrapping cycle counter

Adjustable vertical film carriage speed

Adjustable tension and rotation speed delay

Top of pack overlap control

Microprocessor controlled; display control panel

Ergonomically designed control panel

Options: ramp, pit frame, hold downdevice

(motor driven)

Film	Stretch Polyethylene
Film Thickness	17-35micron
Film Width	500mm
Rotary Table Height	75mm
Rotary Table Height	1650mm
Production Speed	Up to 20 pallets/hr (5.8rpm)*
Pallet Dims	Up to 1200x1000mm
Max Pallet Weight	2000kg
Pallet Height	2200mm
Air Pressure	N/A
Power Supply	240V, Single Phase,50Hz
Power Consumption	1.2kw

Dimensions and specifications will vary according to customer requirements.

* Please note that different turntable sizes will run at different speeds.



Our equipment is widely used in a range of industries including:

Building Products, Can & Bottle, Corrugated & Paper, Food & Beverage, Retail, Timber, Waste Baling, White Goods.